

**TECHNICAL SPECIFICATIONS:**

SUCTION CUP	Capacity	Fastening points	Min. plate dimensions	Movements	Safety devices	Input	Optional	Weight of machine
<a href="#">CUP 2000</a>	185 KG	1						
<a href="#">2P.G</a>	180 kg	2	300x750	Manual rotation	two safety circuits	on request	/	46
<a href="#">2P.G.B</a>	180 kg	2	300x750	Manual rotation and tilt	two safety circuits	on request	/	47
<a href="#">4P.G</a>	360 kg	4	600x800	Manual rotation	two safety circuits	on request	/	56
<a href="#">4P.G.B.</a>	360 kg	4	600x800	Manual rotation and tilt	two safety circuits	on request	three-phase, single-phase, continuous	57
<a href="#">6P.G.</a>	540 kg	6	750x1100	Manual rotation	two safety circuits	on request	three-phase, single-phase, continuous	66
<a href="#">6P.G.B.</a>	540 kg	6	750x1100	Manual rotation and tilt	two safety circuits	on request	three-phase, single-phase, continuous	67
<a href="#">8 P.G.</a>	720 kg	8	750x1400	Manual rotation	two safety circuits	on request	three-phase, single-phase, continuous	76
<a href="#">12 P.G.</a>	1080 kg	12	1100x1400	Manual rotation	two safety circuits	on request	three-phase, single-phase, continuous	96