


Molatrici rettilinee elettroniche per l'esecuzione del **filo piatto con filetti** Electronic straight-line edging machines for the processing of **flat edge with arris**

Elektronischen Kantenbearbeitungsmaschinen zum automatischen Schleifen und Polieren der **flacher Kante mit Saum**

Canteadoras rectilíneas electrónicas para la ejecución de **canto plano con aristas**

Meuleuses rectilignes électroniques pour le façonnage du **joint plat avec arêtes**



AL 5 m	0,5 - 4 m/min	H50 mm	3 - 20 mm	10	5.570x1.200 xH2.400 mm	2.000 Kg	350 kg - 150 kg/m	600 kg
	20 - 157 "/min	H2 "	1/8 - 3/4 "		219.3x47.2 xH94.5 "	4,409 lbs	772 lbs - 8.4 lbs "	1,322 lbs
	5 4 3 2 1							

AL 6 m	0,5 - 4 m/min	H50 mm	3 - 20 mm	12,5	5.570x1.200 xH2.400 mm	2.000 Kg	350 kg - 150 kg/m	600 kg
	20 - 157 "/min	H2 "	1/8 - 3/4 "		219.3x47.2 xH94.5 "	4,409 lbs	772 lbs - 8.4 lbs "	1,322 lbs
	6 5 4 3 2 1							

AL 7 m	0,5 - 4 m/min	H50 mm	3 - 25 mm	14	6.100x1.200 xH2.400 mm	2.200 Kg	400 kg - 150 kg/m	700 kg
	20 - 157 "/min	H2 "	1/8 - 1 "		240.2x47.2 xH94.5 "	4,850 lbs	881 lbs - 8.4 lbs/"	1,543 lbs
	7 6 5 4 3 2 1							

AL 8 m	0,5 - 4 m/min	H50 mm	3 - 25 mm	15	6.100x1.200 xH2.400 mm	2.200 Kg	400 Kg - 150 Kg/m	700 Kg
	20 - 157 "/min	H2 "	1/8 - 1 "		240.2x47.2 xH94.5 "	4,850 lbs	881 lbs - 8.4 lbs"	1,543 lbs
	8 7 6 5 4 3 2 1							

AL 9 m	0,5 - 4 m/min	H50 mm	3 - 25 mm	17	7.140x1.200 xH3.000 mm	2.400 Kg	400 Kg - 150 Kg/m	700 Kg
	20 - 157 "/min	H2 "	1/8 - 1 "		281.1x47.2 xH118.1 "	5,291 lbs	881 lbs - 8.4 lbs/"	1,543 lbs
	9 8 7 6 5 4 3 2 1							

Disponibile anche con impianto cerio
 Available also with cerium oxide equipment

AL 10 m	0,5 - 4 m/min	H50 mm	3 - 25 mm	18,5	7.140x1.200 xH3.000 mm	2.400 Kg	400 Kg - 150 Kg/m	700 Kg
	20 - 157 "/min	H2 "	1/8 - 1 "		281.1x47.2 xH118.1 "	5,291 lbs	811 lbs - 8.4 lbs/"	1,543 lbs
	10 9 8 7 6 5 4 3 2 1							