


Molatrici rettilinee elettroniche per l'esecuzione del **filo piatto con filetti** Electronic straight-line edging machines for the processing of **flat edge with arris**

Elektronischen Kantenbearbeitungsmaschinen zum automatischen Schleifen und Polieren der **flacher Kante mit Saum**
 Canteadoras rectilíneas electrónicas para la ejecución de **canto plano con aristas**
 Meuleuses rectilignes électroniques pour le façonnage du **joint plat avec arêtes**



TLR 10 c dd

0,3 - 5 m/min*	H60 mm	3 - 35 mm** OPTIONAL 3 - 50 mm**	22	8.510x1.350 xH3.100 mm	4.000 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg
12 - 197 "/min*	H2.4 "	1/8 - 1.4 "*** OPTIONAL 1/8 - 2 ""**		335x53.1 xH122 "	8,818 lbs	2,205 lbs - 14 lbs/" OPTIONAL 2,425 lbs - 15.2 lbs/"	4,409 lbs

* max 2 m/min (max 79 "/min) (con spigolatore / with dubbing device)
 ** max 15 mm (max 0.6 ") (con spigolatore / with dubbing device)

TLR 12 c

0,3 - 5 m/min	H60 mm OPTIONAL H35 mm	3 - 35 mm OPTIONAL 3 - 50 mm	23	8.510x1.350 xH3.100 mm	4.000 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg
12 - 197 "/min	H2.4 " OPTIONAL H1.4 "	1/8 - 1.4 " OPTIONAL 1/8 - 2 "		335x53.1 xH122 "	8,818 lbs	2,205 lbs - 14 lbs/" OPTIONAL 2,425 lbs - 15.2 lbs/"	4,409 lbs

OPTIONAL

TLR 13 c


0,3 - 5 m/min	H60 mm OPTIONAL H35 mm	3 - 55 mm	28	9.590x1.350 xH3.100 mm	4.600 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg
12 - 197 "/min	H2.4 " OPTIONAL H1.4 "	1/8 - 2.2 "		377.5x53.1 xH122 "	10,141 lbs	2,205 lbs - 14 lbs/" OPTIONAL 2,425 lbs - 15.2 lbs/"	4,409 lbs

TLR 14 c

0,3 - 5 m/min	H60 mm OPTIONAL H35 mm	3 - 55 mm	30	9.590x1.350 xH3.100 mm	4.800 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg
12 - 197 "/min	H2.4 " OPTIONAL H1.4 "	1/8 - 2.2 "		377.5x53.1 xH122 "	10,582 lbs	2,205 lbs - 14 lbs/" OPTIONAL 2,425 lbs - 15.2 lbs/"	4,409 lbs


TLR 15 c

0,3 - 5 m/min	H60 mm OPTIONAL H35 mm	3 - 55 mm	32	10.020x1.500 xH3.100 mm	5.700 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg
12 - 197 "/min	H2.4 " OPTIONAL H1.4 "	1/8 - 2.2 "		394.5x59.1 xH122 "	12,556 lbs	2,205 lbs - 14 lbs/" OPTIONAL 2,425 lbs - 15.2 lbs/"	4,409 lbs



Molatrici rettilinee elettroniche ad **angolo variabile da 0 a 45°** Electronic straight-line edging machines with **variable angle from 0 up to 45°**

Elektronischen Kantenbearbeitungsmaschinen für normalen **Kanten und Gehrungsschliff von 0 bis 45 Grad**
 Canteadoras rectilíneas electrónicas para la ejecución de **ingletes con inclinaciones de 0 a 45°**
 Meuleuses rectilignes électroniques avec **angle variable de 0 à 45°**



TLR 11 av	0,3 - 5 m/min	H85 mm OPTIONAL H60 mm	0 - 45° OPTIONAL 0 - 60°	3 - 35 mm OPTIONAL 3 - 50 mm	23	8.510x1.350 xH3.100 mm	4.200 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min	H3.3 " OPTIONAL H2.4 "		1/8 - 1.4 " OPTIONAL 1/8 - 2 "		335x53.1 xH122 "	9,259 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	
TLR 11 av c	0,3 - 5 m/min	H85 mm OPTIONAL H60 mm	0 - 45° OPTIONAL 0 - 60°	3 - 35 mm OPTIONAL 3 - 50 mm	23	8.510x1.350 xH3.100 mm	4.200 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min	H3.3 " OPTIONAL H2.4 "		1/8 - 1.4 " OPTIONAL 1/8 - 2 "		335x53.1 xH122 "	9,259 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	
TLR 11 av c dd	0,3 - 5 m/min*	H85 mm	0 - 45°	3 - 55 mm**	25	9.590x1.350 xH3.100 mm	4.800 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min*	H3.3 "		1/8 - 2.2 ""**		377.6x53.1 xH122 "	10,582 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	
<div style="border: 1px solid orange; padding: 5px; display: inline-block;"> <p>* max 2 m/min (max 79 "/min) (con spigolatore / with dubbing device) ** max 15 mm (max 0.6 ") (con spigolatore / with dubbing device)</p> </div>										
TLR 13 av c	0,3 - 5 m/min	H85 mm OPTIONAL H60 mm	0 - 45°	3 - 55 mm	28	9.590x1.350 xH3.100 mm	4.800 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min	H3.3 " OPTIONAL H2.4 "		1/8 - 2.2 "		377.6x53.1 xH122 "	10,582 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	
TLR 14 av c	0,3 - 5 m/min	H85 mm OPTIONAL H60 mm	0 - 45°	3 - 55 mm	30	10.020x1.350 xH3.100 mm	5.700 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min	H3.3 " OPTIONAL H2.4 "		1/8 - 2.2 "		394.5x53.1 xH122 "	12,566 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	
TLR 16 av c	0,3 - 5 m/min	H85 mm OPTIONAL H60 mm	0 - 45°	3 - 55 mm	34	10.370x1.350 xH3.100 mm	6.800 Kg	1.000 Kg - 250 Kg/m OPTIONAL 1.100 Kg - 300 Kg/m	2.000 Kg	
	12 - 197 "/min	H3.3 " OPTIONAL H2.4 "		1/8 - 2.2 "		408.3x53.1 xH122 "	14,991 lbs	2,205 lbs - 14 lbs/ft OPTIONAL 2,425 lbs - 15.2 lbs/ft	4,409 lbs	